

PRODUCT DATASHEET



PAROC XVA 001

Air channel slab

Moulded slab of expanded polystyrene cellular plastic (EPS). When connecting to the outer wall, the Air gap slab can be combined with the PAROC XVA 002 Wind deflector. The air gap slab is pre-grooved for splitting at half-width, but can also easily be formatted to other widths.

Create an air gap in pitched roofs between the insulation and roof underlay. The sheet also acts as a windbreak for the insulation. Moulded expanded polystyrene foam sheet.

Package Type Stretch-film wrapped EUR pallet

DIMENSIONS	
Weight	17 kg/m ³
Thickness	12 mm
Width	1150 mm
Length	850 mm
Height	50 mm

Properties

PROPERTY	VALUE	ACCORDING TO
OTHER PROPERTIES		
Heat conductivity	$\lambda_D = 0,036 \text{ W/m } ^\circ\text{C}$	-
Air gap area	$0,026 \text{ m}^2/\text{cell (c 1200)}$	-
Air permeability	$12 \times 10^3 \text{ s/m}$	-

Head Office: PAROC GROUP, P.O. Box 240 (Energiakuja 3), FI-00181 Helsinki Finland, Tel. +358 46 876 8000, www.paroc.com

The information in this brochure describes the conditions and technical properties of the disclosed products, valid at the time of publication of this document and until replaced by the next printed or digital version. The latest version of this brochure is always available on the Paroc website. Our information material presents applications for which the functions and technical properties of our products have been approved. However, the information does not mean a commercial guarantee. We do not assume liability of the use of third party components used in the application or the installation of our products. We cannot warrant the suitability of our products if used in an area or conditions which are not provided in our information material. As a result of constant further development of our products we reserve the right to make alterations to our information material at any time. PAROC is a registered trademark of Paroc Group. This data sheet is valid in following countries: international use (general information).