

PRODUCT DATASHEET



PAROC XVA 003

Wind diverting shield

Board made of polymer-treated, moisture-protected corrugated cardboard, supplied with creasing instructions.

Wind deflector for eaves. Intended for mounting on secondary insulation. Moisture-proof corrugated cardboard, complete with creasing instructions. Wrap-around in the centre to fit different distances between roof trusses.

Package Type Tied bundles

DIMENSIONS	
Weight	approx. 550 g/m ²
Thickness	approx. 4 mm
Width	650 mm
Length	1255 mm

Properties

PROPERTY	VALUE	ACCORDING TO
FIRE PROPERTIES		
Combustibility	Combustible	EN ISO 1182
OTHER PROPERTIES		
Temperature for use	-20°C – +50°C	

Head Office: PAROC GROUP, P.O. Box 240 (Energiakuja 3), FI-00181 Helsinki Finland, Tel. +358 46 876 8000, www.paroc.com

The information in this brochure describes the conditions and technical properties of the disclosed products, valid at the time of publication of this document and until replaced by the next printed or digital version. The latest version of this brochure is always available on the Paroc website. Our information material presents applications for which the functions and technical properties of our products have been approved. However, the information does not mean a commercial guarantee. We do not assume liability of the use of third party components used in the application or the installation of our products. We cannot warrant the suitability of our products if used in an area or conditions which are not provided in our information material. As a result of constant further development of our products we reserve the right to make alterations to our information material at any time. PAROC is a registered trademark of Paroc Group. This data sheet is valid in following countries: international use (general information).