

DECLARATION OF PERFORMANCE

No. 20008

| | |
|--|--|
| Unique identification code of the product-type | PARAFON Colortone |
| Intended use/es | Suspended ceilings |
| Manufacturer | Paroc Group, Energiakuja 3, FI-00180 Helsinki |
| System/s of AVCP | AVCP 1 for Reaction to fire, AVCP 3 for other properties |
| Harmonised standard | EN 13964:2014 |
| Notified body/ies | No. 0809 - Eurofins Expert Services Ltd |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:
Helsinki 2.7.2020



Paroc Oy Ab, Building Insulation
Susanne Fagerlund, Development Manager

| DURABILITY OF FIRE AND THERMAL PROPERTIES | |
|---|--|
| Durability of Reaction to Fire Against Heat, Weathering, Ageing/Degradation | The fire performance of mineral wool does not deteriorate with time. The Euroclass classification of product is related to the organic content, which cannot increase with time. |

Declared Performance/s

| PROPERTY | VALUE | ACCORDING TO |
|--|------------------------|---|
| REACTION TO FIRE | | |
| Reaction to Fire, Euroclass | A1 | EN 13964:2014 (EN 13501-1) |
| . | Cement: A2-s1,d0 | |
| . | Metal: A2-s2,d0 | |
| ACOUSTIC ABSORPTION INDEX | | |
| Sound Absorption α_w , Construction Depth 200 mm | 15 mm: 0,90 | EN 13964:2014 (EN ISO 354 / EN ISO 11654) |
| . | 40 mm: 1,00 | |
| TENSILE/FLEXURAL STRENGTH | | |
| Flexural Tensile Strength | NPD | EN 13964:2014 |
| OTHER MECHANICAL PROPERTIES | | |
| Shatter Properties | NPD | EN 13964:2014 |
| RELEASE OF DANGEROUS SUBSTANCES TO THE INDOOR ENVIRONMENT | | |
| Release of Formaldehyde | E1 | EN 13964:2014 |
| Release of Asbestos | No content of asbestos | EN 13964:2014 |