

# PAROC BlackCoat Tape

PAROC BlackCoat Tape is a reinforced aluminum foil tape with a black color lacquer finish acrylic pressure sensitive adhesive and siliconized release paper liner.

It is ideal for sealing the joints when using PAROC BlackCoat products such as sections, lamella mats or slabs. PAROC BlackCoat Tape gives a great finish and safe installation.



## Product datasheet

28.8.2025

| Dimensions | Width (mm) | Length (mm) | Thickness (mm) | Rolls / box | Boxes / pallet |
|------------|------------|-------------|----------------|-------------|----------------|
|            | 50         | 50          | 0.068          | 24          | 24             |
|            | 75         | 50          | 0.068          | 16          | 24             |
|            | 110        | 50          | 0.068          | 12          | 24             |

| Product properties | Property          | Value   | Standard reference |
|--------------------|-------------------|---|--------------------|
|                    | Backing           | Glass-scrim reinforced aluminum with black finish | AFERA 5001         |
|                    | Release liner     | Siliconized paper                                 | AFERA 5001         |
|                    | Adhesive          | Acrylic   | AFERA 5001         |
|                    | Adhesive strength | min 20 N / 25 mm after 24 h                       | AFERA 5001         |
|                    | Apply at          | +10°C to +40°C                                    | AFERA 5001         |
|                    | Temperature range | -40°C to +200°C                                   | AFERA 5001         |

| Appearance | Property        | Description  |
|------------|-----------------|--|
|            | Facing material | Glass-scrim reinforced aluminum with black finish, aluminum thickness 0.018 mm |
|            | Colour          | Black  |

| Handling | Item                 | Description  |
|----------|----------------------|--|
|          | Installation         | During the installation, the insulation material to be taped should be at a minimum temperature of +10°C. Allow the temperature of the insulating material to adjust to the ambient installation temperature. Make sure that the surfaces to be joined with tape are clean, dry free of dust, grease and solvents before film/tape application. Do not use cleaners containing anti-adhesive agents. Some plastics and paints may discharge anti-adhesive agents leading to bonding failure. Rough and uneven surfaces may weaken bonding. |
|          | Handling and storage | Product should be stored in original packaging, laid flat on the slit edge of the roll. Storage in dry and clean areas, at normal temperature, protected from direct sunlight and heat sources.<br>Storage conditions: +10°C to +30°C, under dry conditions inside a warehouse, protected from UV.   |

We strongly advise users to test the product's suitability for their own particular requirement. All data and recommendations contained in this Technical Data Sheet are based on our own test results and practical experience and are aimed at helping customers select the appropriate product for a given application.

Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Paroc makes no representation about, and is not responsible or liable for the accuracy or reliability of data associated with particular uses of any product described herein. Paroc reserves the right to modify this document without prior notice. PAROC is a registered trademark of Paroc Group Oy. This data sheet is valid in following countries: International.