

PAROC XIL 002 – Horisontella öppna vindsbjälklag lutning 0°-30°

Deklarerad värmekonduktivitet 0,041 W/mK (säckvikt 15 kg)

Deklarerat värmemotstånd R_D	Deklarerad tjocklek (beställd tjocklek)	Minsta installerad tjocklek	Minimum ytvikt	Minsta antalet säck per 100 m ²
[m ² K/W]	[mm]	[mm]	[kg/m ²]	[säck/100 m ²]
3,7	150	158	6,0	40,0
4,9	200	210	8,0	53,3
7,3	300	315	12,0	80,0
9,8	400	420	16,0	106,7
12,2	500	525	20,0	133,3
14,6	600	630	24,0	160,0
17,1	700	770	28,0	186,7
19,5	800	880	32,0	213,3
22,0	900	990	36,0	240,0
23,2	950	1045	38,0	253,3

PAROC XIL 002 - Slutna utrymmen

Deklarerat lambda 0,036 W/mK (säckvikt 15 kg)

Isolertjocklek 0° - 45°	Deklarerat värmemotstånd R_D	Minsta antalet säck per m ²	Isolertjocklek 45° - 90°	Deklarerat värmemotstånd R_D	Minsta antalet säck per 100 m ²
[mm]	[m ² K/W]	[säck/100 m ²]	[mm]	[m ² K/W]	[säck/100 m ²]
145	4,0	58,0	145	4,0	67,7
170	4,7	68,0	170	4,7	79,3
195	5,4	78,0	195	5,4	91,0
220	6,1	88,0	220	6,1	102,7
240	6,7	96,0	240	6,7	112,0
270	7,5	108,0	270	7,5	126,0
300	8,3	120,0	300	8,3	140,0
350	9,7	140,0	350	9,7	163,3
400	11,1	160,0	400	11,1	186,7
450	12,5	180,0	450	12,5	210,0
500	13,9	200,0			
600	16,7	240,0			

Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Paroc makes no representation about, and is not responsible or liable for the accuracy or reliability of data associated with particular uses of any product described herein. Paroc reserves the right to modify this document without prior notice.

PAROC is a registered trademark of Paroc Group Oy.